Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

Data Sheet
Fujitsu CELSIUS M470 Workstation

Your new "thoroughbred" workstation

CELSIUS M470

The CELSIUS M Series is the single-processor platform with a particularly well-balanced ratio between price and performance. The CELSIUS M470 incorporates the latest advances in performance technologies enabling you to meet increasingly demanding schedules using professional applications such as CAD/CAE, virtual reality and finance.

Performance

Higher productivity

- High performance multi-core processors, hard disk drives and next generation graphics subsystems

Ergonomics

Quiet system for a pleasant working environment

- Optimized thermal management, low-noise chassis and silent fans

Reliability

System stability for the complete lifecycle

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

Certification of workstation applications

Stability, compatibility and performance for the main workstation applications

- Comprehensive support for ISV applications and ease of integration into existing IT networks

Expandability

Excellent expandability for future demands

- Increased memory capacities of up to 24 GB

Components

Processor	Intel® Xeon® processor X5680 (6C, 3.33 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5677 (4C, 3.46 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5670 (6C, 2.93 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5667 (4C, 3.06 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5660 (6C, 2.80 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5650 (6C, 2.66 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5570 (4C, 2.93 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor X5560 (4C, 2.8 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor X5550 (4C, 2.66 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor W5590 (4C, 3.33 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor W3680 (6C, 3.33 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor W3580 (4C, 3.33 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor W3570 (4C, 3.2 GHz, 8 MB, 6.4 GT/s)
	Intel® Xeon® processor W3565 (4C, 3.20 GHz, 8 MB, 4.8 GT/s)
	Intel® Xeon® processor W3550 (4C, 3.06 GHz, 8 MB, 4.8 GT/s)
	Intel® Xeon® processor W3540 (4C, 2.93 GHz, 8 MB, 4.8 GT/s)
	Intel® Xeon® processor W3530 (4C, 2.80 GHz, 8 MB, 4.8 GT/s)
	Intel® Xeon® processor W3520 (4C, 2.66 GHz, 8 MB, 4.8 GT/s)
	Intel® Xeon® processor W3505 (2C, 2.53 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor W3503 (2C, 2.5 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor L5640 (6C, 2.26 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor L5630 (4C, 2.13 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor L5609 (4C, 1.86 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor L5530 (4C, 2.40 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor L5520 (4C, 2.26 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor L5506 (4C, 2.13 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5640 (4C, 2.66 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5630 (4C, 2.53 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5620 (4C, 2.40 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5540 (4C, 2.53 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor E5530 (4C, 2.4 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor E5520 (4C, 2.26 GHz, 8 MB, 5.86 GT/s)
	Intel® Xeon® processor E5507 (4C, 2.26 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5506 (4C, 2.13 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5504 (4C, 2.0 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5503 (2C, 2.00 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor E5502 (2C, 1.86 GHz, 4 MB, 4.8 GT/s)
	Intel® Xeon® processor W3670 (6 Cores / 12 Threads, 3.20 GHz, 12 MB)

Operating system

Operating system optional preinstalled	Genuine Windows® 7 Professional 64-bit Genuine Windows® 7 Professional 32-bit
Operating system compatible	Genuine Windows® XP Professional x64 Edition Genuine Windows® XP Professional Linux
Operating system notes	Red Hat® certification Novell® certification For some configurations third party drivers are currently not available or configuration restrictions may apply.

Memory modules	1 GB (1 module(s) 1 GB) DDR3, 1333 MHz, PC3-10600
	1 GB (1 module(s) 1 GB) DDR3, ECC, 1333 MHz, PC3-10600
	2 GB (1 module(s) 2 GB) DDR3, ECC, 1333 MHz, PC3-10600
	4 GB (1 module(s) 4 GB) DDR3, ECC, 1333 MHz, PC3-10600
Graphics add on cards (optional)	Ultra-high-end 3D: NVIDIA® Quadro® 5000, 2.5 GB, PCIe x16, DL-DVI-I, 2x DP, DVI, VGA
	Ultra-high-end 3D: NVIDIA® Quadro® FX 4800, 1.5 GB, PCIe x16, 2x DL-DVI-I, 2x DP
	High-end 3D: ATI FirePro™ V7800, 2 GB, PCIe x16, DL-DVI-I, 2x DP
	High-end 3D: NVIDIA® Quadro® 4000, 2 GB, PCIe x16, DL-DVI-I, 2x DP
	High-end 3D: NVIDIA® Quadro® FX 3800, 1 GB, PCIe x16, DL-DVI-I, 2x DP
	Midrange 3D: ATI FirePro™ V5800, 1 GB, PCIe x16, DL-DVI-I, 2x DP
	Midrange 3D: NVIDIA® Quadro® 2000, 1 GB, PCIe x16, DL-DVI-I, 2x DP
	Midrange 3D: NVIDIA® Quadro® FX 1800, 768 MB, PCIe x16, DL-DVI-I, 2x DP
	Entry 3D: ATI FirePro™ V4800, 1 GB, PCIe x16, DL-DVI-I, 2x DP
	Entry 3D: NVIDIA® Quadro® 600, 1 GB, PCIe x16, DL-DVI-I, DP
	Entry 3D: NVIDIA® Quadro® FX 580, 512 MB, PCIe x16, DL-DVI-I, 2x DP
	Entry 3D: ATI FirePro™ V3800, 512 MB, PCIe x16, DL-DVI-I, DP
	Entry 3D: NVIDIA® Quadro® FX 380, 256 MB, PCIe x16, 2x DL-DVI-I
	Professional 2D: NVIDIA® Quadro® NVS 450, 512 MB, PCIe x16, 4 x DP
	Professional 2D: NVIDIA® Quadro® NVS 300, 512 MB, PCIe Gen2 x16, 2x DVI/VGA
	Professional 2D: NVIDIA® Quadro® NVS 295, 256 MB, PCIe x16, 2x DP
	Professional 2D: NVIDIA® Quadro® NVS 290, 256 MB, PCIe x16, 2x SL DVI-I
	Multi monitor 2D: NVIDIA® Quadro® NVS 295, 256 MB, PCIe x1, 2x DP
	Multi monitor 2D: NVIDIA® Quadro® NVS 290, 256 MB, PCIe x1, 2x SL DVI-I
	Remote Graphics: CELSIUS RemoteAccess Card, PCIe x1, 2x DVI-I
Hard disk drives (internal)	SSD SATA, 256 GB, 2.5-inch
	SSD SATA, 128 GB, 2.5-inch
	SATA III, 10000 rpm, 600 GB, 3.5-inch internal
	SATA II, 10000 rpm, 300 GB, 2.5-inch, S.M.A.R.T.
	SATA II, 10000 rpm, 150 GB, 2.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 2000 GB, 3.5-inch, S.M.A.R.T. business critical
	SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T. business critical
	SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T. business critical
	SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
	HDD SAS, 15000 rpm, 600 GB, 3.5-inch internal
	HDD SAS, 15000 rpm, 450 GB, 3.5-inch
	HDD SAS, 15000 rpm, 300 GB, 3.5-inch
Hard disk notes	2.5-inch drives will be mounted in the 3.5-inch bays One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
Drives (optional)	Blu-ray Disc™ Triple Writer
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 20in1, 5.25-Inch
	MultiCard Reader 20in1 USB 2.0 5.25-Inch

Interface add on cards/components (optional)		
	WLAN III, 802.11g/Draft-n (Windows only)	
	USB 3.0 PCIe x1	
	Parallel Interface	
	Gigabit Ethernet PCIe x1	
	eSATA Interface	
	Dual serial card PCI	
Base unit	CELSIUS M470-2	CELSIUS M470-2 POWER
Mainboard		
Mainboard type	D2778	
Formfactor	ATX	
Chipset	Intel® X58 Express, Intel® 82801JR ICH10R	
Processor socket	LGA 1366	
Processor quantity maximum	1	
Memory slots	6 DIMM	
Supported capacity RAM (max.)	24 GB	
Memory notes	In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration).	
LAN	Built-in 10/100/1000 MBit/s Realtek RTL8111	
Audio codec	Realtek ALC663	
Audio features	High Definition Audio	
I/O controller on board		
Serial ATA total	6	
SATA RAID support	0, 1, 10, 5	
Interfaces		
Audio: in (rear)	1	
Audio: out / SPDIF (rear)	2 / 1	
Front Audio: in	1	
Front Audio: out	1	
FireWire (IEEE1394) (front)	1	
FireWire (IEEE1394) (rear)	1	
Internal speakers	1	
USB 2.0 total	11	
USB front	2	
USB rear	6	
USB internal	3, thereof 1 type A	
Serial (RS-232)	1	
Mouse / Keyboard (PS/2)	1 / 1	
Ethernet (RJ-45)	1	
Interface Module notes	Anytime USB charge functionality	
Drive bays		
Drive bays total	7	
3.5-inch internal bays	4	
5.25-inch external bays	3	
Slots		
PCI-Express 2.0 x16	2 x (312 mm) full height	
PCI-Express 1.0 x4 (mech. x8)	1 x (312 mm) full height	

Slots		
PCI-Express 2.0 x4 (mech. x8)	1 x (312 mm) full height	
PCI (32-bit / 33 MHz)	2 x (312 mm) full height	
Electrical values		
Power consumption note	190 W depending on configuration	190 W depending on configuration
Rated voltage range	100 V - 240 V	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz
Max. output of single power supply	500 W up to 85% efficiency	700 W up to 85% efficiency
Noise for standard configuration (HDD, ODD, FDD)		
Noise emission	According to ISO9296 (LpAm at bystander position)	
Idle mode	23 dB(A)	
Office mode	23 dB(A)	
Noise notes / description	depending on configuration	
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	215 x 522 x 446 mm	
Operating position	Vertical / horizontal	
Weight	18 kg	
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	15 - 35°C	
Operating relative humidity	10 - 75 %	
Compliance		
Product	CELSIUS M470-2	CELSIUS M470-2 POWER
Model	MCS-D2778	MCS-D2778
Germany	GS depending on configuration Blauer Engel / Blue Angel	GS depending on configuration
Europe	CE	CE
USA/Canada	cCSAus FCC Class B	cCSAus FCC Class B
Global	RoHS (EU & China) ENERGY STAR® 5.0 Medical EMC standard IEC60601-1-2 in combination with medical kit	RoHS (EU & China) ENERGY STAR® 5.0 Medical EMC standard IEC60601-1-2 in combination with medical kit
China	CCC	CCC
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx	https://sp.ts.fujitsu.com/sites/certificates/default.aspx
Security		
Physical security	Kensington Lock support Eye for padlock Seal option Intrusion switch Optional: Integrated cabinet lock	
System security	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Dynamic USB security for full hardware USB protection Control of all USB interfaces External USB interfaces detachable separately Embedded security (TPM 1.2) - Infineon	
User security	Optional: Access protection via internal SmartCard reader User and supervisor BIOS password Optional: SmartCase Logon+	

Additional Software

Additional software (optional)	Drivers & Utilities DVD (DUDVD) Windows® 7 & Vista & XP CyberLink PowerDVD 9 Nero 9 Essentials XL Recovery DVD (Windows® 7) Windows® XP 64 downgrade pack Windows® XP 32 downgrade pack	
	Keyboard on (Special Fujitsu keyboard required) Thermal management	Keyboard on (Special Fujitsu keyboard required) Thermal management
Spare part availability	5 years	5 years

Manageability

Manageability features	DeskUpdate Driver management
Manageability type	DeskView 10.x client management including: DASH 1.1 remote system management
DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration
Supported standards	WMI BootP (made4you) PXE WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability

Input device / components

	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse Space Explorer USB Space Navigator USB Space Pilot USB Keyboard

Warranty

Standard Warranty	3 years (depending on country)
Service level	On-site Service (depending on country)

Maintenance and Support Services - the perfect extension

Recommended Service	5x9, Response Time: Next Business Day
Service Weblink	http://ts.fujitsu.com/Supportservice

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

More information

Fujitsu platform solutions

In addition to Fujitsu CELSIUS M470, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu CELSIUS M470, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com/celsius

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact
FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2010-12-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions